

ELECTRIC LOADER

电动装载机

LCCM



优点:

- 绿色环保:零排放、低噪音, 适配室内及敏感区域, 守护空气与健康
- 经济高效:纯电动、能量回收, 能耗仅为柴油 1/4, 维护简便省成本
- 技术自主:核心自研、三电协同(变速箱/电机/电控), 动力强劲超传统
- 性能可靠:智能调控、稳定输出, 延长寿命、增强扭矩, 设备耐用性提升
- 续航快充:高容量电池、8h 续航, 支持快充, 减少等待, 施工连续有保障
- 智能拓展:能量管理、故障诊断, 预留接口、支持升级, 多元场景皆适配

Advantages:

- Green & Quiet: Zero emissions, low noise; ideal for indoor/noise-sensitive zones, protects air & health.
- Efficient & Economical: Pure electric + energy recovery; 1/4 diesel, low maintenance & costs.
- Homegrown Tech: In-house R&D, 3-electric synergy (trans/motor/ECU); outperforms traditional models.
- Reliable Performance: Smart control for stable output; longer life, stronger torque, better durability.
- Long-Lasting & Quick Charge: 8h battery life, fast charging cuts downtime, ensures non-stop work.
- Future-Ready: Energy/fault management, upgradable design; adapts to all scenarios via smart features.



<http://www.wheel-loader.com>

Tel: +86-053280990582

<http://www.lccmglobal.com>

Email: info@laigong.com



Facebook

技术参数

TECHNICAL PARAMETER

		LG12E	LG16E	LG20E
General Machine Performance 整机参数	Operating weight 整机重量	2600	4200	4300
	Length 长“宽”高	5000x1500x2500	5500x1800x2600	5600x1800x2700
	Wheel base 轴距	2500	2200	2300
	Tire size 轮胎	20.5-15	20.5-16	16/70-20
Bucket Performance 铲斗参数	Rated load 额定	1200	1600	2000
	Standard bucket capacity 标准斗容	0.6	0.8	1
	Bucket width 铲斗宽	1500	1800	1800
	Dumping height 卸载高度	2500	3100	3200
	Dumping reach 卸载距离	600	640	650
	Max. raising height 举升高度	3800	4350	4500
Transmission Performance 变速箱参数	Transmission type 变速箱	Electric special-purpose multifunctional gearbox 电动专用多功能变速箱	Electric special-purpose multifunctional gearbox 电动专用多功能变速箱	Electric special-purpose multifunctional gearbox 电动专用多功能变速箱
Battery data 电池数据	Battery type 电池类型	Lithium iron phosphate 磷酸铁锂	Lithium iron phosphate 磷酸铁锂	Lithium iron phosphate 磷酸铁锂
	Battery capacity 电池容量/kWh	36	50	70
	Drive motor 驱动电机/kW	12	15	25
	Charging voltage 充电电压/V	95	95	95
	Charging time 充电时间/h	4	4	6
	Operating voltage 工作电压 V	65-94	65-94	65-94
	Running time (without interruption) 运行时间(不间断)	6-8h	6-8h	6-8h
	Battery 电池Ah	600	600	600
Control type 控制类型		FNR electronic control FNR电控	FNR electronic control FNR电控	FNR electronic control FNR电控
Drive bridge type 车桥		Electric special-purpose wheel reduction bridge 电动专用轮边桥	Electric special-purpose wheel reduction bridge 电动专用轮边桥	Electric special-purpose wheel reduction bridge 电动专用轮边桥

产品细节

PRODUCT DETAILS



技术参数若有变动, 恕不另行通知, 产品以实图为准, 如有疑问最终解释权归公司所有。
Technical parameters are subject to change without further notice. All products are subject to the physical object. The right of interpretation and final interpretation shall belong to Laigong.